



SHERMAN+REILLY®

DUCT DAWG® AIR UNDERGROUND PULLER

DDHXA-75/100 - 7,500 OR 10,000 LBS. PULLING CAPACITY



- 1** Equipped with an on-board air compressor to tackle multiple jobs with one piece of equipment
- 2** Fully articulating, self-supported 3-axis boom
 - 50 degree swing arc, left and right
 - 90 degree vertical arc, up and down
 - 24 in. telescoping, in and out
 - 17 in. sheave with 60-degree swivel head
- 3** Durable, battery-powered wireless remote control for safer operation
- 4** Digital and manual hydraulic operation interface
- 5** Single engine powering hydraulics and compressor

FEATURES

- Simplified underground jobsite setup
- Optimized, compact design with a footprint under 17 ft.
- Full CANbus compatibility
- Smooth operation with 3-speed gearbox on 75 and 2-speed on 100
- Hydraulically driven, twin capstan bullwheels
- Equipped with a digital recorder to continuously measure length of cable deployed and line tension

DUCT DAWG® UNDERGROUND PULLER

DDHXA-75/100 - 7,500 OR 10,000 LBS. PULLING CAPACITY

Sherman-Reilly.com

SPECIFICATIONS

	DDHXA-75	DDHXA-100
Pulling Capacity Max	7,500 lbs.	10,000 lbs.
Bullwheels	Twin capstan, 6 in. dia., 5-groove followed by 6-groove	Twin capstan, 7 in. dia., 5-groove followed by 6-groove
Gearbox and Line Speed	1st gear 0-60 fpm at 7,500 lbs. with demand payout 2nd gear 0-120 fpm at 3,500 lbs. with demand payout 3rd gear 0-285 fpm at 1,500 lbs. with demand payout	1st gear 0-60 fpm at 10,000 lbs. with demand payout 2nd gear 0-120 fpm at 5,000 lbs. with demand payout
Drive System	Hydraulic	Hydraulic
Hydraulic Fluid	ISO grade 32	ISO grade 32
Hydraulic Reservoir	40 Gallon with cold weather package optional	40 Gallon with cold weather package optional
Engine	71 peak Hp, Diesel, water-cooled, electric start	71 peak Hp, Diesel, water-cooled, electric start
Fuel Capacity	13 Gallons	13 Gallons
Pulling Rope	3/8 in., 6 x 25 XIP IWRC steel wire rope, 2,000 ft.	7/16 in., 6 x 25 XIP IWRC steel wire rope, 2,200 ft.
Boom	Hydraulic, joystick controlled, 3-axis, 50° swing arc - 17 in. sheave with swivel head	Hydraulic, joystick controlled, 3-axis, 50° swing arc - 17 in. sheave with swivel head
Level-wind	Dual automatic fairlead sheaves	Dual automatic fairlead sheaves
Puller Mounted Controls	Dual redundancy hydraulic override	Dual redundancy hydraulic override
Puller Wireless Controls	CANbus controller communicating with radio controlled remote (100 ft. max)	CANbus controller communicating with radio controlled remote (100 ft. max)
Footage Counter	Electronic, actual footage, pay-in and pay-out with memory	Electronic, actual footage, pay-in and pay-out with memory
Hydraulic Tool Circuit	7 gpm @ 2,500 psi auxiliary	7 gpm @ 2,500 psi auxiliary
Pulling Connectors	Rotation-resistant: (1) E-35 rated at 3,000 lbs. & (1) E-49 rated at 8,000 lbs.	Rotation-resistant: (1) rated at 3,000 lbs. & (1) rated at 8,000 lbs.
Frame Construction	Steel tubing, continuous-weld	Steel tubing, continuous-weld
Length, overall, nominal	16 ft. 9 in.	16 ft. 9 in.
Width, overall, nominal	95 in.	95 in.
Height, overall, nominal	114 in.	114 in.
Weight*, nominal	8,900 lbs. with rope	9,100 lbs. with rope
GVWR	9,500 lbs.	9,500 lbs.
Suspension	Leaf-spring	Leaf-spring
Axel Configuration	Single	Single
Wheel Configuration and Tires	Single, LT235/75R17.5	Single, LT235/75R17.5
Brakes, trailer	Electric, with safety break-away switch	Electric, with safety break-away switch
Towing Attachment	3 in. adjustable pintle eye	3 in. adjustable pintle eye
Safety Chains	2 ea. with hooks	2 ea. with hooks
Tie Downs	5/8 in. dia. steel D-rings	5/8 in. dia. steel D-rings
Front / Nose Jack	Hydraulic, with shoe - 144 in. ² of surface area	Hydraulic, with shoe - 144 in. ² of surface area
Stabilizing Jacks	Hydraulic, with shoe at rear corners - 144 in. ² of surface area	Hydraulic, with shoe at rear corners - 144 in. ² of surface area
Electrical System	12 VDC, 90 amp alternator	12 VDC, 90 amp alternator
Lights, navigation	US DOT LED, 12 VDC	US DOT LED, 12 VDC
Battery	12 V	12 V
Grounding	3/4 in. dia. copper-clad steel ground loops (4)	3/4 in. dia. copper-clad steel ground loops (4)
Fire Extinguisher	ABC	ABC
Hose Reel	1 in. by 50 ft.	1 in. by 50 ft.
Air Compressor	Low flow: 160 cfm at 40 psi; High flow: 90 cfm at 90 psi	Low flow: 160 cfm at 40 psi; High flow: 90 cfm at 90 psi

OPTIONS

Strobe Light	
Solar Battery Charger	
Submersible Pumps	Self-priming, compact, high-impact trainer housing pump See utility tools

Air Adapter Kits
Underground Blocks Available



Duct Dawg remote control

© 2018 SHERMAN + REILLY, INC.
REV. 02/19

*Subject to change